

# FILT'RAY 2G 2-month in-line filter

Ref. AT030734

For rinsing medical devices



## DESCRIPTION

**FILT'RAY 2G 2-month in-line filter**

**Ref. AT030734**

AQUATOOLS anti-Legionella and anti-germ in-line filter. Suitable for filtering water to supply equipment used in the treatment of medical devices (e.g. endoscopes).  
 Device: MBS.  
 Membrane type: tubular microfiltration.  
 Membrane: polyethylene.  
 Molecular weight cut-off: 0.1 µm nominal and 0.2 µm absolute sterilizing grade.  
 Qualified water volume per duration of use: 1,320 gallons (6,000 liters).  
 Filtration flow rate: 1.7 gal/min at 43.5 psi and 0.6 gal/min at 14.5 psi (filter only, excludes any flow rate restriction in the faucet).  
 Maximum upstream pressure at the point-of-use: 72.5 psi.  
 Maximum lifespan: 2 months after installation.  
 Thermal shock resistance: 158°F for 30 minutes.  
 Chemical shock resistance: active chlorine levels of up to 100 ppm for 2 hours (cumulative total).  
 Sterile filter.  
 FILT'RAY 2G sterile disposable water filters are:  
 CE marked Class I Medical Devices in Europe that comply with directive 93/42/CEE;  
 Class II Medical Devices in the U.S.A. with FDA-510(K) clearance;  
 Class I Medical Devices in Canada that comply with SOR/98-282.  
 Box of 10. Each filter is individually wrapped and sterile.

## ADVANTAGES



Anti-Legionella and anti-germ



Lifespan: 2 months from installation



Backwash: longer filter life



Rapid installation with no tools required

## TECHNICAL CHARACTERISTICS

**FILT'RAY 2G 2-month in-line filter - Ref. AT030734**

Technology	Point-of-use filtration
Flow rate	1.7 gal/min at 43.5 psi, 0.6 gal/min at 14.5 psi; 6.3 lpm at 3 bar, 2.2 lpm at 1 bar
Lifespan	2 months
Norms	  

