FILT'RAY Compact 3-month handheld shower filter



Ref. AT20361US

Sterile

DESCRIPTION

FILT'RAY Compact 3-month handheld shower filter

Ref. AT20361US

AQUATOOLS anti-Legionella and all-germ shower head filter, shower flow.
Device material: ABS.
Membrane type: tubular microfiltration.
Membrane material: polyethylene.
Molecular weight cut-off: 0.1 µm nominal and 0.2 µm absolute sterilizing grade.
Filtration flow rate: 3.07 gal/min at 43.5 psi and 1.69 gal/min at 14.5 psi (filter only, excludes any flow rate restriction in the faucet).
Maximum upstream pressure at the point-of-use: 72.5 psi.
Maximum lifespan: 3 months from installation.
Thermal shock resistance: 158°F for 30 minutes.
Chemical shock resistance: active chlorine levels of up to 100 ppm for 4 hours (cumulative total).
Sterile filter.
FILT'RAY Compact sterile disposable water filters are:
CE marked Class Is Medical Devices in Europe that comply with European Regulation EU 2017/745 CE Marking year 2023;
Class II Medical Devices in the U.S.A. with FDA-510(K) clearance.
Box of 10. Each filter is individually wrapped and sterile.


ADVANTAGES

- Anti-Legionella and all-germ
- Space-saving
- Lifespan: 3 months after installation

TECHNICAL CHARACTERISTICS

FILT'RAY Compact 3-month handheld shower filter - Ref. AT20361US

Connector	M1/2"
Technology	Point-of-use filtration
Height	3.03 in; 77 mm
Length	7.64 in; 194 mm
Flow rate	1.69 gal/min at 14.5 psi, 3.07 gal/min at 43.5 psi and 2.90 gal/min at 72.5 psi. 6.2 lpm at 1 bar, 11.2 lpm at 3 bar and 13.2 lpm at 5 bar
Diameter	2.2 in; 56 mm
Lifespan	3 months



© AQUATOOLS