# FILT'RAY 1-month wall-mounted shower filter

Ref. AT030777

Sterile




## DESCRIPTION

**FILT'RAY 1-month wall-mounted shower filter**

**Ref. AT030777**

AQUATOOLS anti-Legionella and all-germ shower filter.
Device: ABS.
Membrane type: tubular microfiltration.
Membrane: polyethylene.
Molecular weight cut-off: 0.1 µm nominal and 0.2 µm absolute sterilizing grade.
Filtration flow rate: 3.1 gal/min at 43.5 psi and 1.2 gal/min at 14.5 psi (filter only, excludes any flow rate restriction in the shower).
Maximum upstream pressure at the point-of-use: 72.5 psi.
Maximum lifespan: 1 month from installation.
Thermal shock resistance: 158°F for 30 minutes.
Chemical shock resistance: active chlorine levels of up to 100 ppm for 1 hour (cumulative total).
Sterile filter.
FILT'RAY sterile disposable water filters are:
Class II Medical Devices in the U.S.A. with FDA-510(K) clearance;
Box of 10. Each filter is individually wrapped and sterile.


## ADVANTAGES

- Anti-Legionella and all-germ
- Lifespan : 1 month from installation
- Bubl'air Wash : longer filter life
- Rapid installation with no tools required

## TECHNICAL CHARACTERISTICS

**FILT'RAY 1-month wall-mounted shower filter - Ref. AT030777**

| | |
|---|---|
| Technology | Point-of-use filtration |
| Height | 2.83 in; 72 mm |
| Length | 2.95 in; 75 mm |
| Flow rate | 1.7 gal/min at 43.5 psi, 0.6 gal/min at 14.5 psi; 6.3 lpm at 3 bar, 2.2 lpm at 1 bar |
| Lifespan | 1 month |




© AQUATOOLS