# FILT'RAY 3-month wall-mounted shower filter

Ref. AT030779

Sterile




## DESCRIPTION

**FILT'RAY 3-month wall-mounted shower filter**

**Ref. AT030779**

AQUATOOLS anti-Legionella and all-germ faucet filter.
Device: ABS.
Membrane type: tubular microfiltration.
Membrane: polyethylene.
Molecular weight cut-off: 0.1 µm nominal and 0.2 µm absolute sterilizing grade.
Filtration flow rate: 1.7 gal/min at 43.5 psi and 0.6 gal/min at 14.5 psi (filter only, excludes any flow rate restriction in the faucet).
Maximum upstream pressure at the point-of-use: 72.5 psi.
Maximum lifespan: 3 months after installation.
Thermal shock resistance: 158°F for 30 minutes.
Chemical shock resistance: active chlorine levels of up to 100 ppm for 3 hours (cumulative total).
Sterile filter.
FILT'RAY sterile disposable water filters are:
Class II Medical Devices in the U.S.A. with FDA-510(K) clearance;
Box of 10. Each filter is individually wrapped.


## ADVANTAGES

- Anti-Legionella and all-germ
- Lifespan : 3 months from installation
- Rapid installation with no tools required

## TECHNICAL CHARACTERISTICS

**FILT'RAY 3-month wall-mounted shower filter - Ref. AT030779**

| | |
|---|---|
| Technology | Point-of-use filtration |
| Height | 2.83 in; 72 mm |
| Length | 2.95 in; 75 mm |
| Flow rate | 1.7 gal/min at 43.5 psi, 0.6 gal/min at 14.5 psi; 6.3 lpm at 3 bar, 2.2 lpm at 1 bar |
| Lifespan | 3 months |




© AQUATOOLS